



US009006993B1

(12) **United States Patent**
Timmermans et al.

(10) **Patent No.:** **US 9,006,993 B1**
(45) **Date of Patent:** ***Apr. 14, 2015**

(54) **LIGHT TUBE AND POWER SUPPLY CIRCUIT**

(71) Applicant: **iLumisys, Inc.**, Troy, MI (US)

(72) Inventors: **Jos Timmermans**, Ortonville, MI (US);
Jean C. Raymond, Nominique (CA);
John Ivey, Farmington Hills, MI (US)

(73) Assignee: **iLumisys, Inc.**, Troy, MI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/299,915**

(22) Filed: **Jun. 9, 2014**

Related U.S. Application Data

(63) Continuation of application No. 13/777,331, filed on Feb. 26, 2013, now Pat. No. 8,866,396, which is a continuation of application No. 12/965,019, filed on Dec. 10, 2010, now Pat. No. 8,382,327, which is a

(Continued)

(51) **Int. Cl.**
G05F 1/00 (2006.01)
H05B 33/08 (2006.01)
F21K 99/00 (2010.01)

(52) **U.S. Cl.**
CPC **H05B 33/0815** (2013.01); **F21K 9/17** (2013.01)

(58) **Field of Classification Search**
CPC H05B 33/08; H05B 37/02
USPC 315/224, 246, 291, 185 R
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

| | | |
|-------------|---------|----------------|
| D84,763 S | 7/1931 | Strange |
| D119,797 S | 4/1940 | Winkler et al. |
| D125,312 S | 2/1941 | Logan |
| 2,826,679 A | 3/1958 | Rosenberg |
| 2,909,097 A | 10/1959 | Alden et al. |
| 3,178,622 A | 4/1965 | Paul et al. |
| 3,272,977 A | 9/1966 | Holmes |

(Continued)

FOREIGN PATENT DOCUMENTS

| | | |
|----|---------------|--------|
| DE | 29900320 U1 | 5/1995 |
| DE | 196 51 140 A1 | 6/1997 |

(Continued)

OTHER PUBLICATIONS

Lighting Handbook, 8th Edition, Illuminating Engineering Society of North America, 1993, pp. 237-240.

(Continued)


Primary Examiner — Minh D A

(74) *Attorney, Agent, or Firm* — Young Basile

(57) **ABSTRACT**

A replacement light tube for replacing a fluorescent light tube includes a bulb portion having a first end and a second end, a first end cap and a second end cap disposed at the first end and the second end, respectively, each configured to fit with a socket for the fluorescent light tube, a plurality of light emitting diodes disposed inside and extending between the first and second ends of the bulb portion, wherein the plurality of light emitting diodes is arranged to provide light through at least a portion of the bulb portion and power supply circuitry configured to receive power from a power source and configured to regulate the intensity of light emitted from the plurality of light emitting diodes by pulse-width modulating the received power.

30 Claims, 9 Drawing Sheets



Related U.S. Application Data

continuation of application No. 11/085,744, filed on Mar. 21, 2005, now Pat. No. 8,247,985, which is a continuation of application No. 09/782,375, filed on Feb. 12, 2001, now Pat. No. 7,049,761.

- (60) Provisional application No. 60/181,744, filed on Feb. 11, 2000.

(56)

References Cited

U.S. PATENT DOCUMENTS

| | | | | | | | |
|-----------|---|---------|-------------------|-----------|---|---------|--------------------|
| 3,318,185 | A | 5/1967 | Kott | 4,668,895 | A | 5/1987 | Schneiter |
| 3,561,719 | A | 2/1971 | Grindle | 4,669,033 | A | 5/1987 | Lee |
| 3,586,936 | A | 6/1971 | McLeroy | 4,675,575 | A | 6/1987 | Smith et al. |
| 3,601,621 | A | 8/1971 | Ritchie | 4,682,079 | A | 7/1987 | Sanders et al. |
| 3,612,855 | A | 10/1971 | Juhnke | 4,686,425 | A | 8/1987 | Havel |
| 3,643,088 | A | 2/1972 | Osteen et al. | 4,687,340 | A | 8/1987 | Havel |
| 3,739,336 | A | 6/1973 | Burland | 4,688,154 | A | 8/1987 | Nilssen |
| 3,746,918 | A | 7/1973 | Drucker et al. | 4,688,869 | A | 8/1987 | Kelly |
| 3,818,216 | A | 6/1974 | Larraburu | 4,695,769 | A | 9/1987 | Schweickardt |
| 3,821,590 | A | 6/1974 | Kosman et al. | 4,698,730 | A | 10/1987 | Sakai et al. |
| 3,832,503 | A | 8/1974 | Crane | 4,701,669 | A | 10/1987 | Head et al. |
| 3,858,086 | A | 12/1974 | Anderson et al. | 4,705,406 | A | 11/1987 | Havel |
| 3,909,670 | A | 9/1975 | Wakamatsu et al. | 4,707,141 | A | 11/1987 | Havel |
| 3,924,120 | A | 12/1975 | Cox, III | D293,723 | S | 1/1988 | Buttner |
| 3,958,885 | A | 5/1976 | Stockinger et al. | 4,727,289 | A | 2/1988 | Uchida |
| 3,969,720 | A | 7/1976 | Nishino | 4,727,457 | A | 2/1988 | Thillays |
| 3,974,637 | A | 8/1976 | Bergey et al. | 4,739,454 | A | 4/1988 | Federgreen |
| 3,993,386 | A | 11/1976 | Rowe | 4,740,882 | A | 4/1988 | Miller |
| 4,001,571 | A | 1/1977 | Martin | 4,748,545 | A | 5/1988 | Schmitt |
| 4,009,394 | A | 2/1977 | Mierzwinski | 4,753,148 | A | 6/1988 | Johnson |
| 4,054,814 | A | 10/1977 | Fegley et al. | 4,758,173 | A | 7/1988 | Northrop |
| 4,070,568 | A | 1/1978 | Gala | 4,765,708 | A | 8/1988 | Becker et al. |
| 4,082,395 | A | 4/1978 | Donato et al. | 4,767,172 | A | 8/1988 | Hubble, III et al. |
| 4,096,349 | A | 6/1978 | Donato | 4,771,274 | A | 9/1988 | Havel |
| 4,102,558 | A | 7/1978 | Krachman | 4,780,621 | A | 10/1988 | Bartleucci et al. |
| 4,107,581 | A | 8/1978 | Abernethy | 4,794,373 | A | 12/1988 | Harrison |
| 4,189,663 | A | 2/1980 | Schmutzer et al. | 4,794,383 | A | 12/1988 | Havel |
| 4,211,955 | A | 7/1980 | Ray | 4,801,928 | A | 1/1989 | Minter |
| 4,241,295 | A | 12/1980 | Williams, Jr. | 4,810,937 | A | 3/1989 | Havel |
| 4,257,672 | A | 3/1981 | Balliet | 4,818,072 | A | 4/1989 | Mohebban |
| 4,261,029 | A | 4/1981 | Mousset | 4,824,269 | A | 4/1989 | Havel |
| 4,262,255 | A | 4/1981 | Kokei et al. | 4,837,565 | A | 6/1989 | White |
| 4,271,408 | A | 6/1981 | Teshima et al. | 4,843,627 | A | 6/1989 | Stebbins |
| 4,271,458 | A | 6/1981 | George, Jr. | 4,845,481 | A | 7/1989 | Havel |
| 4,272,689 | A | 6/1981 | Crosby et al. | 4,845,745 | A | 7/1989 | Havel |
| 4,273,999 | A | 6/1981 | Pierpoint | 4,847,536 | A | 7/1989 | Lowe et al. |
| 4,298,869 | A | 11/1981 | Okuno | 4,851,972 | A | 7/1989 | Altman |
| 4,329,625 | A | 5/1982 | Nishizawa et al. | 4,854,701 | A | 8/1989 | Noll et al. |
| 4,339,788 | A | 7/1982 | White et al. | 4,857,801 | A | 8/1989 | Farrell |
| 4,342,947 | A | 8/1982 | Bloyd | 4,863,223 | A | 9/1989 | Weissenbach et al. |
| 4,344,117 | A | 8/1982 | Niccum | 4,870,325 | A | 9/1989 | Kazar |
| 4,367,464 | A | 1/1983 | Kurahashi et al. | 4,874,320 | A | 10/1989 | Freed et al. |
| D268,134 | S | 3/1983 | Zurcher | 4,887,074 | A | 12/1989 | Simon et al. |
| 4,382,272 | A | 5/1983 | Quella et al. | 4,894,832 | A | 1/1990 | Colak |
| 4,388,567 | A | 6/1983 | Yamazaki et al. | 4,901,207 | A | 2/1990 | Sato et al. |
| 4,388,589 | A | 6/1983 | Moldrem, Jr. | 4,904,988 | A | 2/1990 | Nesbit et al. |
| 4,392,187 | A | 7/1983 | Bornhorst | 4,912,371 | A | 3/1990 | Hamilton |
| 4,394,719 | A | 7/1983 | Moberg | 4,920,459 | A | 4/1990 | Rothwell et al. |
| 4,420,711 | A | 12/1983 | Takahashi et al. | 4,922,154 | A | 5/1990 | Cacoub |
| 4,455,562 | A | 6/1984 | Dolan et al. | 4,929,936 | A | 5/1990 | Friedman et al. |
| 4,500,796 | A | 2/1985 | Quin | 4,934,852 | A | 6/1990 | Havel |
| 4,521,835 | A | 6/1985 | Meggs et al. | 4,941,072 | A | 7/1990 | Yasumoto et al. |
| 4,531,114 | A | 7/1985 | Topol et al. | 4,943,900 | A | 7/1990 | Gartner |
| 4,581,687 | A | 4/1986 | Nakanishi | 4,962,687 | A | 10/1990 | Belliveau et al. |
| 4,597,033 | A | 6/1986 | Meggs et al. | 4,965,561 | A | 10/1990 | Havel |
| 4,600,972 | A | 7/1986 | MacIntyre | 4,973,835 | A | 11/1990 | Kurosu et al. |
| 4,607,317 | A | 8/1986 | Lin | 4,977,351 | A | 12/1990 | Bavaro et al. |
| 4,622,881 | A | 11/1986 | Rand | 4,979,081 | A | 12/1990 | Leach et al. |
| 4,625,152 | A | 11/1986 | Nakai | 4,979,180 | A | 12/1990 | Muncheryan |
| 4,635,052 | A | 1/1987 | Aoike et al. | 4,980,806 | A | 12/1990 | Taylor et al. |
| 4,647,217 | A | 3/1987 | Havel | 4,991,070 | A | 2/1991 | Stob |
| 4,650,971 | A | 3/1987 | Manecchi et al. | 4,992,704 | A | 2/1991 | Stinson |
| 4,656,398 | A | 4/1987 | Michael et al. | 5,001,609 | A | 3/1991 | Gardner et al. |
| 4,661,890 | A | 4/1987 | Watanabe et al. | 5,003,227 | A | 3/1991 | Nilssen |
| | | | | 5,008,595 | A | 4/1991 | Kazar |
| | | | | 5,008,788 | A | 4/1991 | Palinkas |
| | | | | 5,010,459 | A | 4/1991 | Taylor et al. |
| | | | | 5,018,054 | A | 5/1991 | Ohashi et al. |
| | | | | 5,027,037 | A | 6/1991 | Wei |
| | | | | 5,027,262 | A | 6/1991 | Freed |
| | | | | 5,032,960 | A | 7/1991 | Katoh |
| | | | | 5,034,807 | A | 7/1991 | Von Kohorn |
| | | | | 5,036,248 | A | 7/1991 | McEwan et al. |
| | | | | 5,038,255 | A | 8/1991 | Nishihashi et al. |
| | | | | 5,065,226 | A | 11/1991 | Kluitmans et al. |
| | | | | 5,072,216 | A | 12/1991 | Grange |
| | | | | 5,078,039 | A | 1/1992 | Tulk et al. |
| | | | | 5,083,063 | A | 1/1992 | Brooks |
| | | | | 5,088,013 | A | 2/1992 | Revis |

(56)

References Cited

U.S. PATENT DOCUMENTS

| | | | | | | | |
|-----------|---|---------|--------------------|-----------|---|---------|--------------------|
| 5,089,748 | A | 2/1992 | Ihms | 5,519,496 | A | 5/1996 | Borgert et al. |
| 5,103,382 | A | 4/1992 | Kondo et al. | 5,530,322 | A | 6/1996 | Ference et al. |
| 5,122,733 | A | 6/1992 | Havel | 5,539,628 | A | 7/1996 | Seib |
| 5,126,634 | A | 6/1992 | Johnson | 5,544,809 | A | 8/1996 | Keating et al. |
| 5,128,595 | A | 7/1992 | Hara | 5,545,950 | A | 8/1996 | Cho |
| 5,130,761 | A | 7/1992 | Tanaka | 5,550,440 | A | 8/1996 | Allison et al. |
| 5,130,909 | A | 7/1992 | Gross | 5,559,681 | A | 9/1996 | Duarte |
| 5,134,387 | A | 7/1992 | Smith et al. | 5,561,346 | A | 10/1996 | Byrne |
| 5,136,483 | A | 8/1992 | Schoniger et al. | D376,030 | S | 11/1996 | Cohen |
| 5,140,220 | A | 8/1992 | Hasegawa | 5,575,459 | A | 11/1996 | Anderson |
| 5,142,199 | A | 8/1992 | Elwell | 5,575,554 | A | 11/1996 | Guritz |
| 5,151,679 | A | 9/1992 | Dimmick | 5,581,158 | A | 12/1996 | Quazi |
| 5,154,641 | A | 10/1992 | McLaughlin | 5,592,051 | A | 1/1997 | Korkala |
| 5,161,879 | A | 11/1992 | McDermott | 5,592,054 | A | 1/1997 | Nerone et al. |
| 5,161,882 | A | 11/1992 | Garrett | 5,600,199 | A | 2/1997 | Martin, Sr. et al. |
| 5,164,715 | A | 11/1992 | Kashiwabara et al. | 5,607,227 | A | 3/1997 | Yasumoto et al. |
| 5,184,114 | A | 2/1993 | Brown | 5,608,290 | A | 3/1997 | Hutchisson et al. |
| 5,194,854 | A | 3/1993 | Havel | 5,614,788 | A | 3/1997 | Mullins et al. |
| 5,198,756 | A | 3/1993 | Jenkins et al. | 5,621,282 | A | 4/1997 | Haskell |
| 5,209,560 | A | 5/1993 | Taylor et al. | 5,621,603 | A | 4/1997 | Adamec et al. |
| 5,220,250 | A | 6/1993 | Szuba | 5,621,662 | A | 4/1997 | Humphries et al. |
| 5,225,765 | A | 7/1993 | Callahan et al. | 5,622,423 | A | 4/1997 | Lee |
| 5,226,723 | A | 7/1993 | Chen | 5,633,629 | A | 5/1997 | Hochstein |
| 5,254,910 | A | 10/1993 | Yang | 5,634,711 | A | 6/1997 | Kennedy et al. |
| 5,256,948 | A | 10/1993 | Boldin et al. | 5,639,158 | A | 6/1997 | Sato |
| 5,268,828 | A | 12/1993 | Miura | 5,640,061 | A | 6/1997 | Bornhorst et al. |
| 5,278,542 | A | 1/1994 | Smith et al. | 5,640,141 | A | 6/1997 | Myllymaki |
| 5,282,121 | A | 1/1994 | Bornhorst et al. | 5,640,792 | A | 6/1997 | O'Shea |
| 5,283,517 | A | 2/1994 | Havel | 5,642,129 | A | 6/1997 | Zavracky et al. |
| 5,287,352 | A | 2/1994 | Jackson et al. | 5,655,830 | A | 8/1997 | Ruskouski |
| 5,294,865 | A | 3/1994 | Haraden | 5,656,935 | A | 8/1997 | Havel |
| 5,298,871 | A | 3/1994 | Shimohara | 5,661,374 | A | 8/1997 | Cassidy et al. |
| 5,301,090 | A | 4/1994 | Hed | 5,661,645 | A | 8/1997 | Hochstein |
| 5,303,124 | A | 4/1994 | Wrobel | 5,673,059 | A | 9/1997 | Zavracky et al. |
| 5,307,295 | A | 4/1994 | Taylor et al. | 5,682,103 | A | 10/1997 | Burrell |
| 5,321,593 | A | 6/1994 | Moates | 5,684,523 | A | 11/1997 | Satoh et al. |
| 5,323,226 | A | 6/1994 | Schreder | 5,688,042 | A | 11/1997 | Madadi et al. |
| 5,329,431 | A | 7/1994 | Taylor et al. | 5,690,417 | A | 11/1997 | Choate |
| 5,344,068 | A | 9/1994 | Haessig | 5,697,695 | A | 12/1997 | Lin et al. |
| 5,350,977 | A | 9/1994 | Hamamoto et al. | 5,701,058 | A | 12/1997 | Roth |
| 5,357,170 | A | 10/1994 | Luchaco et al. | 5,712,650 | A | 1/1998 | Barlow |
| 5,365,411 | A | 11/1994 | Rycroft et al. | 5,713,655 | A | 2/1998 | Blackman |
| 5,371,618 | A | 12/1994 | Tai et al. | 5,721,471 | A | 2/1998 | Begemann et al. |
| 5,374,876 | A | 12/1994 | Horibata et al. | 5,725,148 | A | 3/1998 | Hartman |
| 5,375,043 | A | 12/1994 | Tokunaga | 5,726,535 | A | 3/1998 | Yan |
| D354,360 | S | 1/1995 | Murata | 5,731,759 | A | 3/1998 | Finucan |
| 5,381,074 | A | 1/1995 | Rudzewicz et al. | 5,734,590 | A | 3/1998 | Tebbe |
| 5,388,357 | A | 2/1995 | Malita | 5,751,118 | A | 5/1998 | Mortimer |
| 5,402,702 | A | 4/1995 | Hata | 5,752,766 | A | 5/1998 | Bailey et al. |
| 5,404,094 | A | 4/1995 | Green et al. | 5,765,940 | A | 6/1998 | Levy et al. |
| 5,404,282 | A | 4/1995 | Klinke et al. | 5,769,527 | A | 6/1998 | Taylor et al. |
| 5,406,176 | A | 4/1995 | Sugden | 5,784,006 | A | 7/1998 | Hochstein |
| 5,410,328 | A | 4/1995 | Yoksa et al. | 5,785,227 | A | 7/1998 | Akiba |
| 5,412,284 | A | 5/1995 | Moore et al. | 5,790,329 | A | 8/1998 | Klaus et al. |
| 5,412,552 | A | 5/1995 | Fernandes | 5,803,579 | A | 9/1998 | Turnbull et al. |
| 5,420,482 | A | 5/1995 | Phares | 5,803,580 | A | 9/1998 | Tseng |
| 5,421,059 | A | 6/1995 | Leffers, Jr. | 5,803,729 | A | 9/1998 | Tsimerman |
| 5,430,356 | A | 7/1995 | Ference et al. | 5,806,965 | A | 9/1998 | Deese |
| 5,432,408 | A | 7/1995 | Matsuda et al. | 5,808,689 | A | 9/1998 | Small |
| 5,436,535 | A | 7/1995 | Yang | 5,810,463 | A | 9/1998 | Kawahara et al. |
| 5,436,853 | A | 7/1995 | Shimohara | 5,812,105 | A | 9/1998 | Van de Ven |
| 5,450,301 | A | 9/1995 | Waltz et al. | 5,813,751 | A | 9/1998 | Shaffer |
| 5,461,188 | A | 10/1995 | Drago et al. | 5,813,753 | A | 9/1998 | Vriens et al. |
| 5,463,280 | A | 10/1995 | Johnson | 5,821,695 | A | 10/1998 | Vilanilam et al. |
| 5,463,502 | A | 10/1995 | Savage, Jr. | 5,825,051 | A | 10/1998 | Bauer et al. |
| 5,465,144 | A | 11/1995 | Parker et al. | 5,828,178 | A | 10/1998 | York et al. |
| 5,473,522 | A | 12/1995 | Kriz et al. | 5,831,522 | A | 11/1998 | Weed et al. |
| 5,475,300 | A | 12/1995 | Havel | 5,836,676 | A | 11/1998 | Ando et al. |
| 5,481,441 | A | 1/1996 | Stevens | 5,841,177 | A | 11/1998 | Komoto et al. |
| 5,489,827 | A | 2/1996 | Xia | 5,848,837 | A | 12/1998 | Gustafson |
| 5,491,402 | A | 2/1996 | Small | 5,850,126 | A | 12/1998 | Kanbar |
| 5,493,183 | A | 2/1996 | Kimball | 5,851,063 | A | 12/1998 | Doughty et al. |
| 5,504,395 | A | 4/1996 | Johnson et al. | 5,852,658 | A | 12/1998 | Knight et al. |
| 5,506,760 | A | 4/1996 | Giebler et al. | 5,854,542 | A | 12/1998 | Forbes |
| 5,513,082 | A | 4/1996 | Asano | RE36,030 | E | 1/1999 | Nadeau |
| | | | | 5,859,508 | A | 1/1999 | Ge et al. |
| | | | | 5,865,529 | A | 2/1999 | Yan |
| | | | | 5,870,233 | A | 2/1999 | Benz et al. |
| | | | | 5,890,794 | A | 4/1999 | Abtahi et al. |

(56)

References Cited

U.S. PATENT DOCUMENTS

| | | | | | | | |
|-----------|----|----------|------------------------------|-----------|----|---------|--------------------|
| 5,893,633 | A | 4/1999 | Saito et al. | 6,183,104 | B1 | 2/2001 | Ferrara |
| 5,896,010 | A | 4/1999 | Mikolajczak et al. | 6,184,628 | B1 | 2/2001 | Ruthenberg |
| 5,904,415 | A | 5/1999 | Robertson et al. | 6,196,471 | B1 | 3/2001 | Ruthenberg |
| 5,907,742 | A | 5/1999 | Johnson et al. | 6,203,180 | B1 | 3/2001 | Fleischmann |
| 5,909,378 | A | 6/1999 | De Milleville | 6,211,626 | B1 | 4/2001 | Lys et al. |
| 5,912,653 | A | 6/1999 | Fitch | 6,215,409 | B1 | 4/2001 | Blach |
| 5,917,287 | A | 6/1999 | Haederle et al. | 6,217,190 | B1 | 4/2001 | Altman et al. |
| 5,917,534 | A | 6/1999 | Rajeswaran | 6,219,239 | B1 | 4/2001 | Mellberg et al. |
| 5,921,660 | A | 7/1999 | Yu | 6,227,679 | B1 | 5/2001 | Zhang et al. |
| 5,924,784 | A | * 7/1999 | Chliwnyj et al. 362/234 | 6,234,645 | B1 | 5/2001 | Börner et al. |
| 5,927,845 | A | 7/1999 | Gustafson et al. | 6,238,075 | B1 | 5/2001 | Dealey, Jr. et al. |
| 5,934,792 | A | 8/1999 | Camarota | 6,240,665 | B1 | 6/2001 | Brown et al. |
| 5,936,599 | A | 8/1999 | Reymond | 6,241,359 | B1 | 6/2001 | Lin |
| 5,939,830 | A | 8/1999 | Praiswater | 6,249,221 | B1 | 6/2001 | Reed |
| 5,943,802 | A | 8/1999 | Tijanic | 6,250,774 | B1 | 6/2001 | Begemann et al. |
| 5,946,209 | A | 8/1999 | Eckel et al. | 6,252,350 | B1 | 6/2001 | Alvarez |
| 5,949,347 | A | 9/1999 | Wu | 6,252,358 | B1 | 6/2001 | Xydis et al. |
| 5,951,145 | A | 9/1999 | Iwasaki et al. | 6,268,600 | B1 | 7/2001 | Nakamura et al. |
| 5,952,680 | A | 9/1999 | Strite | 6,273,338 | B1 | 8/2001 | White |
| 5,959,547 | A | 9/1999 | Tubel et al. | 6,292,901 | B1 | 9/2001 | Lys et al. |
| 5,961,072 | A | 10/1999 | Bodle | 6,297,724 | B1 | 10/2001 | Bryans et al. |
| 5,962,989 | A | 10/1999 | Baker | 6,305,109 | B1 | 10/2001 | Lee |
| 5,962,992 | A | 10/1999 | Huang et al. | 6,305,821 | B1 | 10/2001 | Hsieh et al. |
| 5,963,185 | A | 10/1999 | Havel | 6,307,331 | B1 | 10/2001 | Bonasia et al. |
| 5,966,069 | A | 10/1999 | Zmurk et al. | 6,310,590 | B1 | 10/2001 | Havel |
| 5,974,553 | A | 10/1999 | Gandar | 6,315,429 | B1 | 11/2001 | Grandolfo |
| 5,980,064 | A | 11/1999 | Metroyanis | 6,323,832 | B1 | 11/2001 | Nishizawa et al. |
| 5,998,925 | A | 12/1999 | Shimizu et al. | 6,325,651 | B1 | 12/2001 | Nishihara et al. |
| 5,998,928 | A | 12/1999 | Hipp | 6,334,699 | B1 | 1/2002 | Gladnick |
| 6,000,807 | A | 12/1999 | Moreland | 6,340,868 | B1 | 1/2002 | Lys et al. |
| 6,007,209 | A | 12/1999 | Pelka | 6,362,578 | B1 | 3/2002 | Swanson et al. |
| 6,008,783 | A | 12/1999 | Kitagawa et al. | 6,371,637 | B1 | 4/2002 | Atchinson et al. |
| 6,010,228 | A | 1/2000 | Blackman et al. | 6,380,865 | B1 | 4/2002 | Pederson |
| 6,011,691 | A | 1/2000 | Schreffler | 6,394,623 | B1 | 5/2002 | Tsui |
| 6,016,038 | A | 1/2000 | Mueller et al. | 6,400,096 | B1 | 6/2002 | Wells et al. |
| 6,018,237 | A | 1/2000 | Havel | 6,404,131 | B1 | 6/2002 | Kawano et al. |
| 6,019,493 | A | 2/2000 | Kuo et al. | 6,411,045 | B1 | 6/2002 | Nerone |
| 6,020,825 | A | 2/2000 | Chansky et al. | 6,429,604 | B1 | 8/2002 | Chang |
| 6,025,550 | A | 2/2000 | Kato | 6,445,139 | B1 | 9/2002 | Marshall et al. |
| 6,028,694 | A | 2/2000 | Schmidt | 6,459,919 | B1 | 10/2002 | Lys et al. |
| 6,030,099 | A | 2/2000 | McDermott | 6,464,373 | B1 | 10/2002 | Petrick |
| 6,031,343 | A | 2/2000 | Recknagel et al. | 6,469,457 | B2 | 10/2002 | Callahan |
| 6,031,958 | A | 2/2000 | McGaffigan | 6,471,388 | B1 | 10/2002 | Marsh |
| 6,036,335 | A | 3/2000 | Openiano | 6,495,964 | B1 | 12/2002 | Muthu et al. |
| 6,036,336 | A | 3/2000 | Wu | 6,511,204 | B2 | 1/2003 | Emmel et al. |
| D422,737 | S | 4/2000 | Orozco | 6,528,954 | B1 | 3/2003 | Lys et al. |
| 6,056,420 | A | 5/2000 | Wilson et al. | 6,540,381 | B1 | 4/2003 | Douglass, II |
| 6,068,383 | A | 5/2000 | Robertson et al. | 6,541,800 | B2 | 4/2003 | Barnett et al. |
| 6,069,597 | A | 5/2000 | Hansen | 6,548,967 | B1 | 4/2003 | Dowling et al. |
| 6,072,280 | A | 6/2000 | Allen | 6,568,834 | B1 | 5/2003 | Scianna |
| 6,084,359 | A | 7/2000 | Hetzel et al. | 6,577,072 | B2 | 6/2003 | Saito et al. |
| 6,086,220 | A | 7/2000 | Lash et al. | 6,577,080 | B2 | 6/2003 | Lys et al. |
| 6,091,200 | A | 7/2000 | Lenz | 6,577,794 | B1 | 6/2003 | Currie et al. |
| 6,092,915 | A | 7/2000 | Rensch | 6,582,103 | B1 | 6/2003 | Popovich et al. |
| 6,095,661 | A | 8/2000 | Lebens et al. | 6,585,393 | B1 | 7/2003 | Brandes et al. |
| 6,097,352 | A | 8/2000 | Zavracky et al. | 6,608,453 | B2 | 8/2003 | Morgan et al. |
| 6,115,184 | A | 9/2000 | Hubble, III et al. | 6,609,813 | B1 | 8/2003 | Showers et al. |
| 6,116,748 | A | 9/2000 | George | 6,612,729 | B1 | 9/2003 | Hoffman |
| 6,121,875 | A | 9/2000 | Hamm et al. | 6,621,222 | B1 | 9/2003 | Hong |
| 6,127,783 | A | 10/2000 | Pashley et al. | 6,624,597 | B2 | 9/2003 | Dowling et al. |
| 6,132,072 | A | 10/2000 | Turnbull et al. | 6,682,205 | B2 | 1/2004 | Lin |
| 6,135,604 | A | 10/2000 | Lin | 6,712,486 | B1 | 3/2004 | Popovich et al. |
| 6,135,620 | A | 10/2000 | Marsh | 6,717,376 | B2 | 4/2004 | Lys et al. |
| 6,139,174 | A | 10/2000 | Butterworth | 6,720,745 | B2 | 4/2004 | Lys et al. |
| 6,149,283 | A | 11/2000 | Conway et al. | 6,736,525 | B2 | 5/2004 | Chin |
| 6,150,774 | A | 11/2000 | Mueller et al. | 6,762,562 | B2 | 7/2004 | Leong |
| 6,151,529 | A | 11/2000 | Batko | 6,768,047 | B2 | 7/2004 | Chang et al. |
| 6,153,985 | A | 11/2000 | Grossman | 6,774,584 | B2 | 8/2004 | Lys et al. |
| 6,158,882 | A | 12/2000 | Bischoff, Jr. | 6,777,891 | B2 | 8/2004 | Lys et al. |
| 6,166,496 | A | 12/2000 | Lys et al. | 6,781,329 | B2 | 8/2004 | Mueller et al. |
| 6,175,201 | B1 | 1/2001 | Sid | 6,788,011 | B2 | 9/2004 | Mueller et al. |
| 6,175,220 | B1 | 1/2001 | Billig et al. | 6,796,680 | B1 | 9/2004 | Showers et al. |
| 6,181,126 | B1 | 1/2001 | Havel | 6,806,659 | B1 | 10/2004 | Mueller et al. |
| D437,947 | S | 2/2001 | Huang | 6,853,151 | B2 | 2/2005 | Leong et al. |
| 6,183,086 | B1 | 2/2001 | Neubert | 6,869,204 | B2 | 3/2005 | Morgan et al. |
| | | | | 6,888,322 | B2 | 5/2005 | Dowling et al. |
| | | | | 6,897,624 | B2 | 5/2005 | Lys et al. |
| | | | | 6,936,978 | B2 | 8/2005 | Morgan et al. |
| | | | | 6,953,261 | B1 | 10/2005 | Jiao et al. |

(56)

References Cited

U.S. PATENT DOCUMENTS

| | | | | | | | |
|--------------|-----|---------|----------------------------------|--------------|----|---------|------------------------|
| 6,965,205 | B2 | 11/2005 | Piegras et al. | 2003/0222587 | A1 | 12/2003 | Dowling, Jr. et al. |
| 6,967,448 | B2 | 11/2005 | Morgan et al. | 2004/0052076 | A1 | 3/2004 | Mueller et al. |
| 6,975,079 | B2 | 12/2005 | Lys et al. | 2004/0085219 | A1 | 5/2004 | Pederson |
| 7,014,336 | B1 | 3/2006 | Ducharme et al. | 2004/0090191 | A1 | 5/2004 | Mueller et al. |
| 7,031,920 | B2 | 4/2006 | Dowling et al. | 2004/0105261 | A1 | 6/2004 | Ducharme et al. |
| 7,038,398 | B1 | 5/2006 | Lys et al. | 2004/0145490 | A1 | 7/2004 | Pederson |
| 7,049,761 | B2* | 5/2006 | Timmermans et al. 315/246 | 2004/0155609 | A1 | 8/2004 | Lys et al. |
| 7,064,498 | B2 | 6/2006 | Dowling et al. | 2004/0178751 | A1 | 9/2004 | Mueller et al. |
| 7,102,902 | B1 | 9/2006 | Brown et al. | 2004/0212320 | A1 | 10/2004 | Dowling et al. |
| 7,113,541 | B1 | 9/2006 | Lys et al. | 2004/0212993 | A1 | 10/2004 | Morgan et al. |
| 7,120,560 | B2 | 10/2006 | Williams et al. | 2004/0240890 | A1 | 12/2004 | Lys et al. |
| 7,132,785 | B2 | 11/2006 | Ducharme | 2004/0257007 | A1 | 12/2004 | Lys et al. |
| 7,132,804 | B2 | 11/2006 | Lys et al. | 2005/0030744 | A1 | 2/2005 | Ducharme et al. |
| 7,135,824 | B2 | 11/2006 | Lys et al. | 2005/0041161 | A1 | 2/2005 | Dowling et al. |
| 7,139,617 | B1 | 11/2006 | Morgan et al. | 2005/0041424 | A1 | 2/2005 | Ducharme |
| 7,161,311 | B2 | 1/2007 | Mueller et al. | 2005/0043907 | A1 | 2/2005 | Eckel et al. |
| 7,161,313 | B2 | 1/2007 | Piegras et al. | 2005/0044617 | A1 | 3/2005 | Mueller et al. |
| 7,180,252 | B2 | 2/2007 | Lys et al. | 2005/0047132 | A1 | 3/2005 | Dowling et al. |
| 7,186,003 | B2 | 3/2007 | Dowling et al. | 2005/0047134 | A1 | 3/2005 | Mueller et al. |
| 7,187,141 | B2 | 3/2007 | Mueller et al. | 2005/0062440 | A1 | 3/2005 | Lys et al. |
| 7,221,104 | B2 | 5/2007 | Lys et al. | 2005/0063194 | A1 | 3/2005 | Lys et al. |
| 7,231,060 | B2 | 6/2007 | Dowling et al. | 2005/0099317 | A1 | 5/2005 | Pederson |
| 7,233,831 | B2 | 6/2007 | Blackwell | 2005/0151489 | A1 | 7/2005 | Lys et al. |
| 7,242,152 | B2 | 7/2007 | Dowling et al. | 2005/0166634 | A1 | 8/2005 | Lieberman et al. |
| 7,248,239 | B2 | 7/2007 | Dowling et al. | 2005/0174473 | A1 | 8/2005 | Morgan et al. |
| 7,253,566 | B2 | 8/2007 | Lys et al. | 2005/0184667 | A1 | 8/2005 | Sturman et al. |
| 7,255,457 | B2 | 8/2007 | Ducharme et al. | 2005/0236998 | A1 | 10/2005 | Mueller et al. |
| 7,274,160 | B2 | 9/2007 | Mueller et al. | 2005/0285547 | A1 | 12/2005 | Piegras et al. |
| 7,308,296 | B2 | 12/2007 | Lys et al. | 2006/0012987 | A9 | 1/2006 | Ducharme et al. |
| 7,309,965 | B2 | 12/2007 | Dowling et al. | 2006/0016960 | A1 | 1/2006 | Morgan et al. |
| 7,344,278 | B2 | 3/2008 | Paravantsos | 2006/0050509 | A9 | 3/2006 | Dowling et al. |
| 7,350,936 | B2 | 4/2008 | Ducharme et al. | 2006/0109649 | A1 | 5/2006 | Ducharme et al. |
| 7,353,071 | B2 | 4/2008 | Blackwell et al. | 2006/0152172 | A9 | 7/2006 | Mueller et al. |
| 7,385,359 | B2 | 6/2008 | Dowling et al. | 2006/0285325 | A1 | 12/2006 | Ducharme et al. |
| 7,401,935 | B2 | 7/2008 | VanderSchuit | 2007/0030683 | A1 | 2/2007 | Popovich et al. |
| 7,427,840 | B2 | 9/2008 | Morgan et al. | 2007/0047227 | A1 | 3/2007 | Ducharme |
| 7,510,299 | B2 | 3/2009 | Timmermans et al. | 2007/0086754 | A1 | 4/2007 | Lys et al. |
| 7,598,686 | B2 | 10/2009 | Lys et al. | 2007/0086912 | A1 | 4/2007 | Dowling et al. |
| 7,600,907 | B2 | 10/2009 | Liu et al. | 2007/0115658 | A1 | 5/2007 | Mueller et al. |
| RE42,161 | E | 2/2011 | Hochstein | 2007/0115665 | A1 | 5/2007 | Mueller et al. |
| 8,093,823 | B1 | 1/2012 | Ivey et al. | 2007/0188427 | A1 | 8/2007 | Lys et al. |
| 8,247,985 | B2* | 8/2012 | Timmermans et al. 315/246 | 2007/0195526 | A1 | 8/2007 | Dowling et al. |
| 8,382,327 | B2* | 2/2013 | Timmermans et al. ... 362/249.02 | 2007/0258240 | A1 | 11/2007 | Ducharme et al. |
| 8,482,212 | B1 | 7/2013 | Ivey et al. | 2008/0012506 | A1 | 1/2008 | Mueller et al. |
| 2001/0033488 | A1 | 10/2001 | Chliwnyj et al. | 2011/0109454 | A1 | 5/2011 | McSheffrey, Sr. et al. |
| 2002/0011801 | A1 | 1/2002 | Chang | 2013/0200797 | A1 | 8/2013 | Timmermans et al. |
| 2002/0047569 | A1 | 4/2002 | Dowling et al. | | | | |
| 2002/0047628 | A1 | 4/2002 | Morgan et al. | | | | |
| 2002/0048169 | A1 | 4/2002 | Dowling et al. | | | | |
| 2002/0048174 | A1 | 4/2002 | Pederson | | | | |
| 2002/0057061 | A1 | 5/2002 | Mueller et al. | | | | |
| 2002/0070688 | A1 | 6/2002 | Dowling et al. | | | | |
| 2002/0074559 | A1 | 6/2002 | Dowling et al. | | | | |
| 2002/0074958 | A1 | 6/2002 | Crenshaw | | | | |
| 2002/0078221 | A1 | 6/2002 | Blackwell et al. | | | | |
| 2002/0101197 | A1 | 8/2002 | Lys et al. | | | | |
| 2002/0113555 | A1 | 8/2002 | Lys et al. | | | | |
| 2002/0130627 | A1 | 9/2002 | Morgan et al. | | | | |
| 2002/0152045 | A1 | 10/2002 | Dowling et al. | | | | |
| 2002/0153851 | A1 | 10/2002 | Morgan et al. | | | | |
| 2002/0158583 | A1 | 10/2002 | Lys et al. | | | | |
| 2002/0163316 | A1 | 11/2002 | Lys et al. | | | | |
| 2002/0171365 | A1 | 11/2002 | Morgan et al. | | | | |
| 2002/0171377 | A1 | 11/2002 | Mueller et al. | | | | |
| 2002/0171378 | A1 | 11/2002 | Morgan et al. | | | | |
| 2002/0176259 | A1 | 11/2002 | Ducharme | | | | |
| 2003/0011538 | A1 | 1/2003 | Lys et al. | | | | |
| 2003/0057884 | A1 | 3/2003 | Dowling et al. | | | | |
| 2003/0057886 | A1 | 3/2003 | Lys et al. | | | | |
| 2003/0057887 | A1 | 3/2003 | Dowling et al. | | | | |
| 2003/0057890 | A1 | 3/2003 | Lys et al. | | | | |
| 2003/0076281 | A1 | 4/2003 | Morgan et al. | | | | |
| 2003/0100837 | A1 | 5/2003 | Lys et al. | | | | |
| 2003/0133292 | A1 | 7/2003 | Mueller et al. | | | | |
| 2003/0137258 | A1 | 7/2003 | Piegras et al. | | | | |

FOREIGN PATENT DOCUMENTS

| | | | |
|----|------------|----|---------|
| DE | 196 24 087 | A1 | 12/1997 |
| DE | 299 00 320 | U1 | 5/1999 |
| DE | 298 17 609 | U1 | 1/2000 |
| EP | 0 091 172 | A2 | 10/1983 |
| EP | 0 124 924 | B1 | 9/1987 |
| EP | 0 174 699 | B1 | 11/1988 |
| EP | 0 197 602 | B1 | 11/1990 |
| EP | 0 390 262 | B1 | 12/1993 |
| EP | 0 359 329 | B1 | 3/1994 |
| EP | 0 403 011 | B1 | 4/1994 |
| EP | 0 632 511 | A2 | 1/1995 |
| EP | 0 432 848 | B1 | 4/1995 |
| EP | 0 525 876 | B1 | 5/1996 |
| EP | 0 714 556 | B1 | 1/1999 |
| EP | 0 889 283 | A1 | 7/1999 |
| EP | 0 458 408 | B1 | 9/1999 |
| EP | 0 578 302 | B1 | 9/1999 |
| GB | 2 165977 | A | 4/1986 |
| GB | 2 215 024 | A | 9/1989 |
| GB | 2 324 901 | A | 11/1998 |
| JP | S62-241382 | A | 10/1987 |
| JP | S62-248271 | A | 10/1987 |
| JP | H05-102530 | A | 4/1993 |
| JP | H6-54103 | | 7/1994 |
| JP | 07-249467 | A | 9/1995 |
| JP | 07-264036 | A | 10/1995 |
| JP | 08-162677 | A | 6/1996 |
| JP | H8-162677 | | 6/1996 |
| JP | 10-308536 | A | 11/1998 |
| JP | H11-135274 | | 5/1999 |

(56)

References Cited

FOREIGN PATENT DOCUMENTS

| | | | |
|----|------------|----|---------|
| JP | 11-162234 | A | 6/1999 |
| JP | H11-162234 | A | 6/1999 |
| JP | H11-260125 | A | 9/1999 |
| JP | 5102530 | B2 | 12/2012 |
| WO | 99/06759 | A1 | 2/1999 |
| WO | 99/10867 | A1 | 3/1999 |
| WO | 99/31560 | A2 | 6/1999 |
| WO | 99/45312 | A1 | 9/1999 |
| WO | 99/57945 | A1 | 11/1999 |
| WO | 00/01067 | A2 | 1/2000 |

OTHER PUBLICATIONS

Petition for Inter Partes Review of U.S. Patent No. 7,510,299, IPR # 2014-00710 filed Apr. 30, 2014 in 2135 pages. (uploaded in ten parts due to EFS size limits).

Petition for Inter Partes Review of U.S. Patent No. 8,382,327, IPR # 2014-01120 filed Jul. 3, 2014 in 854 pages. (uploaded in fifteen parts due to EFS size limits).

Claim charts submitted in initial invalidity contentions served on May 8, 2014 in Civil Case No. 2:13-cv-14961 (E.D. Mich.) in 174 pages.

Petition for Inter Partes Review of U.S. Patent No. 8093823, IPR # 2014-00448 filed Feb. 19, 2014 in 1175 pages. (uploaded in three parts due to EFS size limits).

Defendant's Invalidation Contentions in *Altair Engineering, Inc. v. LEDSAmerica, Inc.*, Civil Case No. 2:10-Cv-13424 (E. D. Mich.)(J. O'Meara)(Feb. 4, 2011).

Decision in *Altair Engineering, Inc. v. LEDdynamics* (Fed. Cir. Mar. 9, 2011).

Web page at http://trucklite.com/leds_14.htm printed on Jan. 13, 2000.

Web page at http://trucklite.com/leds_2.htm printed on Jan. 13, 2000.

Web page at http://trucklite.com/leds_4.htm printed on Jan. 13, 2000.

Web page at http://www.telecite.com/en/products/options_en.htm printed on Jan. 13, 2000.


Web page at <http://www.dialight.com/trans.htm> printed on Jan. 13, 2000.

Web page at <http://www.ledlight.com/replac.htm> printed on Jan. 13, 2000.

LEDtronics, apparently 1996 Catalog, apparently cover page and p. 10.

Petition for Inter Partes Review of U.S. Patent No. 7,049,761, IPR # 2014-01333 filed Aug. 19, 2014 in 757 pages. (uploaded in ten parts due to EFS size limits).

* cited by examiner






FIG-2




FIG-3




FIG-4





FIG-5






FIG-7




FIG-8





FIG-9



LIGHT TUBE AND POWER SUPPLY CIRCUIT**CROSS-REFERENCE TO RELATED APPLICATIONS**

This is a continuation of U.S. patent application Ser. No. 13/777,331, filed Feb. 26, 2013, which is a continuation of U.S. patent application Ser. No. 12/965,019, filed Dec. 10, 2010 and issued as U.S. Pat. No. 8,382,327 on Feb. 26, 2013, which is a continuation of U.S. patent application Ser. No. 11/085,744, filed Mar. 21, 2005 and issued as U.S. Pat. No. 8,247,985 on Aug. 21, 2012, which is a continuation of U.S. patent application Ser. No. 09/782,375, filed Feb. 12, 2001 and issued as U.S. Pat. No. 7,049,761 on May 23, 2006, which claims the benefit of U.S. Provisional Application No. 60/181,744 filed Feb. 11, 2000.

FIELD OF THE INVENTION

The present invention relates to a light tube illuminated by LEDs (light emitting diodes) which are packaged inside the light tube and powered by a power supply circuit.

BACKGROUND OF THE INVENTION

Conventional fluorescent lighting systems include fluorescent light tubes and ballasts. Such lighting systems are used in a variety of locations, such as buildings and transit buses, for a variety of lighting purposes, such as area lighting or back-lighting. Although conventional fluorescent lighting systems have some advantages over known lighting options, such as incandescent lighting systems, conventional fluorescent light tubes and ballasts have several shortcomings. Conventional fluorescent light tubes have a short life expectancy, are prone to fail when subjected to excessive vibration, consume high amounts of power, require a high operating voltage, and include several electrical connections which reduce reliability. Conventional ballasts are highly prone to fail when subjected to excessive vibration. Accordingly, there is a desire to provide a light tube and power supply circuit which overcome the shortcomings of conventional fluorescent lighting systems. That is, there is a desire to provide a light tube and power supply circuit which have a long life expectancy, are resistant to vibration failure, consume low amounts of power, operate on a low voltage, and are highly reliable. It would also be desirable for such a light tube to mount within a conventional fluorescent light tube socket.

SUMMARY OF THE INVENTION

Embodiments of a replacement light tube for replacing a fluorescent light tube are disclosed herein. In one embodiment, the replacement light tube includes a bulb portion having a first end and a second end, a first end cap and a second end cap disposed at the first end and the second end, respectively, each configured to fit with a socket for the fluorescent light tube and a plurality of light emitting diodes disposed inside and extending between the first and second ends of the bulb portion. The plurality of light emitting diodes is arranged to provide light through at least a portion of the bulb portion. The replacement light tube also includes power supply circuitry configured to receive power from a power source and configured to regulate the intensity of light emitted from the plurality of light emitting diodes by pulse-width modulating the received power.

In another embodiment, the replacement light tube includes a housing having a first end and a second end, a first

end cap and a second end cap disposed at the first end and the second end, respectively, each configured to fit with a socket for the fluorescent light tube and a plurality of light emitting diodes disposed inside and extending between the first and second ends of the housing. The plurality of light emitting diodes is arranged to provide light through at least a portion of the housing. The replacement light tube also includes a pulse width modulator configured to receive power from a power source and configured to regulate the intensity of light emitted from the plurality of light emitting diodes by cyclically switching the received power on and off according to a varying duty cycle.

In another embodiment, the replacement light tube includes a housing having a first end and a second end, a first end cap and a second end cap disposed at the first end and the second end, respectively, each configured to fit with a socket for the fluorescent light tube and a plurality of light emitting diodes disposed inside and extending between the first and second ends of the housing. The plurality of light emitting diodes is arranged to provide light through at least a portion of the housing. The replacement light tube also includes a pulse width modulator configured to regulate the intensity of light emitted from the plurality of light emitting diodes by cyclically switching the received power on and off according to a varying duty cycle and configured to compensate for at least one white light intensity-affecting factor by using the cyclically-switched power.

Embodiments of a replacement light tube for replacing a fluorescent light tube are disclosed herein where the replacement light tube includes a bulb portion having a first end and a second end, a first end cap and a second end cap disposed at the first end and the second end, respectively, each configured to fit with a socket for the fluorescent light tube, a plurality of light emitting diodes disposed inside and extending between the first and second ends of the bulb portion and power supply circuitry having a pulse-width modulator. In one embodiment, the method includes receiving power from a power source and regulating the intensity of light emitted from the plurality of light emitting diodes. Regulating the intensity includes cyclically switching, using the pulse-width modulator, the received power on and off according to a varying duty cycle.

These and other embodiments will be discussed in additional detail hereafter.

BRIEF DESCRIPTION OF THE DRAWINGS

The description herein makes reference to the accompanying drawings wherein like reference numerals refer to like parts throughout the several views, and wherein:

FIG. 1 is a line drawing showing a light tube, in perspective view, which in accordance with the present invention is illuminated by LEDs packaged inside the light tube;

FIG. 2 is a perspective view of the LEDs mounted on a circuit board;

FIG. 3 is a cross-sectional view of FIG. 2 taken along lines 3-3;

FIG. 4 is a fragmentary, perspective view of one embodiment of the present invention showing one end of the light tube disconnected from one end of a light tube socket;

FIG. 5 is an electrical block diagram of a first power supply circuit for supplying power to the light tube;

FIG. 6 is an electrical schematic of a switching power supply type current limiter;

FIG. 7 is an electrical block diagram of a second power supply circuit for supplying power to the light tube;

3

FIG. 8 is an electrical block diagram of a third power supply circuit for supplying power to the light tube;

FIG. 9 is a fragmentary, perspective view of another embodiment of the present invention showing one end of the light tube disconnected from one end of the light tube socket; and

FIG. 10 is an electrical block diagram of a fourth power supply circuit for supplying power to the light tube.

DETAILED DESCRIPTION

FIG. 1 is a line drawing showing a light tube 20 in perspective view. In accordance with the present invention, the light tube 20 is illuminated by LEDs 22 packaged inside the light tube 20. The light tube 20 includes a cylindrically shaped bulb portion 24 having a pair of end caps 26 and 28 disposed at opposite ends of the bulb portion. Preferably, the bulb portion 24 is made from a transparent or translucent material such as glass, plastic, or the like. As such, the bulb material may be either clear or frosted.

In a preferred embodiment of the present invention, the light tube 20 has the same dimensions and end caps 26 and 28 (e.g. electrical male bi-pin connectors, type G13) as a conventional fluorescent light tube. As such, the present invention can be mounted in a conventional fluorescent light tube socket.

The line drawing of FIG. 1 also reveals the internal components of the light tube 20. The light tube 20 further includes a circuit board 30 with the LEDs 22 mounted thereon. The circuit board 30 and LEDs 22 are enclosed inside the bulb portion 24 and the end caps 26 and 28.

FIG. 2 is a perspective view of the LEDs 22 mounted on the circuit board 30. A group of LEDs 22, as shown in FIG. 2, is commonly referred to as a bank or array of LEDs. Within the scope of the present invention, the light tube 20 may include one or more banks or arrays of LEDs 22 mounted on one or more circuit boards 30. In a preferred embodiment of the present invention, the LEDs 22 emit white light and, thus, are commonly referred to in the art as white LEDs. In FIGS. 1 and 2, the LEDs 22 are mounted to one surface 32 of the circuit board 30. In a preferred embodiment of the present invention, the LEDs 22 are arranged to emit or shine white light through only one side of the bulb portion 24, thus directing the white light to a predetermined point of use. This arrangement reduces light losses due to imperfect reflection in a conventional lighting fixture. In alternative embodiments of the present invention, LEDs 22 may also be mounted, in any combination, to the other surfaces 34, 36, and/or 38 of the circuit board 30.

FIG. 3 is a cross-sectional view of FIG. 2 taken along lines 3-3. To provide structural strength along the length of the light tube 20, the circuit board 30 is designed with a H-shaped cross-section. To produce a predetermined radiation pattern or dispersion of light from the light tube 20, each LED 22 is mounted at an angle relative to adjacent LEDs and/or the mounting surface 32. The total radiation pattern of light from the light tube 20 is effected by (1) the mounting angle of the LEDs 22 and (2) the radiation pattern of light from each LED. Currently, white LEDs having a viewing range between 6° and 45° are commercially available.

FIG. 4 is a fragmentary, perspective view of one embodiment of the present invention showing one end of the light tube 20 disconnected from one end of a light tube socket 40. Similar to conventional fluorescent lighting systems and in this embodiment of the present invention, the light tube

4

socket 40 includes a pair of electrical female connectors 42 and the light tube 20 includes a pair of mating electrical male connectors 44.

Within the scope of the present invention, the light tube 20 may be powered by one of four power supply circuits 100, 200, 300, and 400. A first power supply circuit includes a power source and a conventional fluorescent ballast. A second power supply circuit includes a power source and a rectifier/filter circuit. A third power supply circuit includes a DC power source and a PWM (Pulse Width Modulation) circuit. A fourth power supply circuit powers the light tube 20 inductively.

FIG. 5 is an electrical block diagram of a first power supply circuit 100 for supplying power to the light tube 20. The first power supply circuit 100 is particularly adapted to operate within an existing, conventional fluorescent lighting system. As such, the first power supply circuit 100 includes a conventional fluorescent light tube socket 40 having two electrical female connectors 42 disposed at opposite ends of the socket. Accordingly, a light tube 20 particularly adapted for use with the first power supply circuit 100 includes two end caps 26 and 28, each end cap having the form of an electrical male connector 44 which mates with a corresponding electrical female connector 42 in the socket 40.

The first power supply circuit 100 also includes a power source 46 and a conventional magnetic or electronic fluorescent ballast 48. The power source 46 supplies power to the conventional fluorescent ballast 48.

The first power supply circuit 100 further includes a rectifier/filter circuit 50, a PWM circuit 52, and one or more current-limiting circuits 54. The rectifier/filter circuit 50, the PWM circuit 52, and the one or more current-limiting circuits 54 of the first power supply circuit 100 are packaged inside one of the two end caps 26 or 28 of the light tube 20.

The rectifier/filter circuit 50 receives AC power from the ballast 48 and converts the AC power to DC power. The PWM circuit 52 receives the DC power from the rectifier/filter circuit 50 and pulse-width modulates the DC power to the one or more current-limiting circuits 54. In a preferred embodiment of the present invention, the PWM circuit 52 receives the DC power from the rectifier/filter circuit 50 and cyclically switches the DC power on and off to the one or more current-limiting circuits 54. The DC power is switched on and off by the PWM circuit 52 at a frequency which causes the white light emitted from the LEDs 22 to appear, when viewed with a "naked" human eye, to shine continuously. The PWM duty cycle can be adjusted or varied by control circuitry (not shown) to maintain the power consumption of the LEDs 22 at safe levels.

The DC power is modulated for several reasons. First, the DC power is modulated to adjust the brightness or intensity of the white light emitted from the LEDs 22 and, in turn, adjust the brightness or intensity of the white light emitted from the light tube 20. Optionally, the brightness or intensity of the white light emitted from the light tube 20 may be adjusted by a user. Second, the DC power is modulated to improve the illumination efficiency of the light tube 20 by capitalizing upon a phenomenon in which short pulses of light at high brightness or intensity to appear brighter than a continuous, lower brightness or intensity of light having the same average power. Third, the DC power is modulated to regulate the intensity of light emitted from the light tube 20 to compensate for supply voltage fluctuations, ambient temperature changes, and other such factors that affect the intensity of white light emitted by the LEDs 22. Fourth, the DC power is modulated to raise the variations of the frequency of light above the nominal variation of 120 to 100 Hz thereby reduc-

5

ing illumination artifacts caused by low frequency light variations, including interactions with video screens. Fifth, the DC power may optionally be modulated to provide an alarm function wherein light from the light tube 20 cyclically flashes on and off.

The one or more current-limiting circuits 54 receive the pulse-width modulated or switched DC power from the PWM circuit 52 and transmit a regulated amount of power to one or more arrays of LEDs 22. Each current-limiting circuit 54 powers a bank of one or more white LEDs 22. If a bank of LEDs 22 consists of more than one LED, the LEDs are electrically connected in series in an anode to cathode arrangement. If brightness or intensity variation between the LEDs 22 can be tolerated, the LEDs can be electrically connected in parallel.

The one or more current-limiting circuits 54 may include (1) a resistor, (2) a current-limiting semiconductor circuit, or (3) a switching power supply type current limiter.

FIG. 6 is an electrical schematic of a switching power supply type current limiter 56. The limiter 56 includes an inductor 58, electrically connected in series between the PWM circuit 52 and the array of LEDs 22, and a power diode 60, electrically connected between ground 62 and a PWM circuit/inductor node 64. The diode 60 is designed to begin conduction after the PWM circuit 52 is switched off. In this case, the value of the inductor 58 is adjusted in conjunction with the PWM duty cycle to provide the benefits described above. The switching power supply type current limiter 56 provides higher power efficiency than the other types of current-limiting circuits listed above.

FIG. 7 is an electrical block diagram of a second power supply circuit 200 for supplying power to the light tube 20. Similar to the first power supply circuit 100, the second power supply circuit 200 includes a conventional fluorescent light tube socket 40 having two electrical female connectors 42 disposed at opposite ends of the socket 40. Accordingly, a light tube 20 particularly adapted for use with the second power supply circuit 200 includes two end caps 26 and 28, each end cap having the form of an electrical male connector 44 which mates with a corresponding electrical female connector 42 in the socket 40.

In the second power supply circuit 200, the power source 46 supplies power directly to the rectifier/filter circuit 50. The rectifier/filter circuit 50, the PWM circuit 52, and the one or more current-limiting circuits 54 operate as described above to power the one or more arrays of LEDs 22. The rectifier/filter circuit 50, the PWM circuit 52, and the one or more current-limiting circuits 54 of the second power supply circuit 200 are preferably packaged inside the end caps 26 and 28 or the bulb portion 24 of the light tube 20 or inside the light tube socket 40.

FIG. 8 is an electrical block diagram of a third power supply circuit 300 for supplying power to the light tube 20. Similar to the first and second power supply circuits 100 and 200, the third power supply circuit 300 includes a conventional fluorescent light tube socket 40 having two electrical female connectors 42 disposed at opposite ends of the socket 40. Accordingly, a light tube 20 particularly adapted for use with the third power supply circuit 300 includes two end caps 26 and 28, each end cap having the form of an electrical male connector 44 which mates with a corresponding electrical female connector 42 in the socket 40.

The third power supply circuit 300 includes a DC power source 66, such as a vehicle battery. In the third power supply circuit 300, the DC power source 66 supplies DC power directly to the PWM circuit 52. The PWM circuit 52 and the one or more current-limiting circuits 54 operate as described

6

above to power the one or more arrays of LEDs 22. In the third power supply circuit 300, the PWM circuit 52 is preferably packaged in physical location typically occupied by the ballast of a conventional fluorescent lighting system while the one or more current-limiting circuits 54 and LEDs 22 are preferably packaged inside the light tube 20, in either one of the two end caps 26 or 28 or the bulb portion 24.

FIG. 9 is a fragmentary, perspective view of another embodiment of the present invention showing one end of the light tube 20 disconnected from one end of the light tube socket 40. In this embodiment of the present invention, the light tube socket 40 includes a pair of brackets 68 and the light tube 20 includes a pair of end caps 26 and 28 which mate with the brackets 68.

FIG. 10 is an electrical block diagram of a fourth power supply circuit 400 for supplying power to the light tube 20. Unlike the first, second, and third power supply circuits 100, 200, and 300 which are powered through direct electrical male and female connectors 44 and 42, the fourth power supply circuit 400 is powered inductively. As such, the fourth power supply circuit 400 includes a light tube socket 40 having two brackets 68 disposed at opposite ends of the socket 40. At least one bracket 68 includes an inductive transmitter 70. Accordingly, a light tube 20 particularly adapted for use with the fourth power supply circuit 400 has two end caps 26 and 28 with at least one end cap including an inductive receiver or antenna 72. When the light tube 20 is mounted in the light tube socket 40, the at least one inductive receiver 72 in the light tube 20 is disposed adjacent to the at least one inductive transmitter 70 in the light tube socket 40.

The fourth power supply circuit 400 includes the power source 46 which supplies power to the at least one inductive transmitter 70 in the light tube socket 40. The at least one transmitter 70 inductively supplies power to the at least one receiver 72 in one of the end caps 26 and/or 28 of the light tube 20. The at least one inductive receiver 72 supplies power to the rectifier/filter circuit 50. The rectifier/filter circuit 50, PWM circuit 52, and the one or more current-limiting circuits 54 operate as described above to power the one or more arrays of LEDs 22. In this manner, the light tube 20 is powered without direct electrical connection.

What is claimed is:

1. A replacement light tube for replacing a fluorescent light tube, comprising:
 - a bulb portion having a first end and a second end;
 - a first end cap and a second end cap disposed at the first end and the second end, respectively, each configured to fit with a socket for the fluorescent light tube;
 - a plurality of light emitting diodes disposed inside and extending between the first and second ends of the bulb portion, wherein the plurality of light emitting diodes is arranged to provide light through at least a portion of the bulb portion; and
 - power supply circuitry configured to receive power from a power source and configured to regulate the intensity of light emitted from the plurality of light emitting diodes by pulse-width modulating the received power.
2. The replacement light tube of claim 1, wherein the power supply circuitry is configured to regulate the intensity of light emitted from the plurality of light emitting diodes to compensate for voltage fluctuations from the power source.
3. The replacement light tube of claim 1, wherein the power supply circuitry is configured to regulate the intensity of light emitted from the plurality of light emitting diodes to compensate for ambient temperature changes.

7

4. The replacement light tube of claim 1, wherein at least a portion of the power supply circuitry is packaged inside the bulb portion.

5. The replacement light tube of claim 1, wherein the power supply circuitry includes a pulse width modulator configured to receive the power from the power source and configured to regulate the intensity of light emitted from the plurality of light emitting diodes by pulse-width modulating the received power and a current limiter having an inductive element electrically coupled between the pulse width modulator and at least some of the plurality of light emitting diodes, the current limiter configured to receive power from the pulse width modulator and to transmit power to the at least some of the plurality of light emitting diodes.

6. The replacement light tube of claim 5, wherein the current limiter and the pulse width modulator are packaged outside of the bulb portion.

7. The replacement light tube of claim 1, wherein the power supply circuitry is configured to switch power to the plurality of light emitting diodes on and off at a frequency and to cause the light emitted from the plurality of light emitting diodes to appear, when viewed by a human eye, to shine continuously.

8. The replacement light tube of claim 1, further comprising:

a rigid support structure having a planar portion having a first surface extending within the bulb portion between the first end and the second end and having spaced-apart sidewalls extending away from the first surface and extending within the bulb portion between the first end and the second end, at least a portion of the sidewalls in contact with an interior surface of the bulb portion.

9. The replacement light tube of claim 8, wherein the plurality of light emitting diodes are supported by a second surface of the planar portion opposite to the first surface and between the first end and the second end.

10. A replacement light tube for replacing a fluorescent light tube, comprising:

a housing having a first end and a second end;

a first end cap and a second end cap disposed at the first end and the second end, respectively, each configured to fit with a socket for the fluorescent light tube;

a plurality of light emitting diodes disposed inside and extending between the first and second ends of the housing, wherein the plurality of light emitting diodes is arranged to provide light through at least a portion of the housing; and

a pulse width modulator configured to receive power from a power source and configured to regulate the intensity of light emitted from the plurality of light emitting diodes by cyclically switching the received power on and off according to a varying duty cycle.

11. The replacement light tube of claim 10, wherein the pulse width modulator is configured to regulate the intensity of light emitted from the plurality of light emitting diodes to compensate for voltage fluctuations from the power source.

12. The replacement light tube of claim 10, wherein the pulse width modulator is configured to regulate the intensity of light emitted from the plurality of light emitting diodes to compensate for ambient temperature changes.

13. The replacement light tube of claim 10, further comprising:

a current limiter having an inductive element electrically coupled between the pulse width modulator and at least some of the plurality of light emitting diodes, the current limiter configured to receive power from the pulse width modulator and to transmit power to the at least some of the plurality of light emitting diodes.

8

14. The replacement light tube of claim 13, wherein the current limiter and the pulse width modulator are packaged outside of the housing.

15. The replacement light tube of claim 10, further comprising:

a rigid support structure having a planar portion having a first surface extending within the housing between the first end and the second end and having spaced-apart sidewalls extending away from the first surface and extending within the housing between the first end and the second end, at least a portion of the sidewalls in contact with an interior surface of the housing.

16. The replacement light tube of claim 15, wherein the plurality of light emitting diodes are supported by a second surface of the planar portion opposite to the first surface and between the first end and the second end.

17. A method for operating a replacement light tube for replacing a fluorescent light tube, the replacement light tube including:

a bulb portion having a first end and a second end;

a first end cap and a second end cap disposed at the first end and the second end, respectively, each configured to fit with a socket for the fluorescent light tube;

a plurality of light emitting diodes disposed inside and extending between the first and second ends of the bulb portion; and

power supply circuitry having a pulse-width modulator, the method comprising:

receiving power from a power source; and

regulating the intensity of light emitted from the plurality of light emitting diodes, wherein regulating the intensity comprises:

cyclically switching, using the pulse-width modulator, the received power on and off according to a varying duty cycle.

18. The method for operating the replacement light tube of claim 17, wherein regulating the intensity comprises:

regulating the intensity of light emitted from the plurality of light emitting diodes by cyclically switching, using the pulse-width modulator, the received power on and off according to a varying duty cycle to compensate for voltage fluctuations from the power source.

19. The method for operating the replacement light tube of claim 17, wherein regulating the intensity comprises:

regulating the intensity of light emitted from the plurality of light emitting diodes by cyclically switching, using the pulse-width modulator, the received power on and off according to a varying duty cycle to compensate for ambient temperature changes.

20. The method for operating the replacement light tube of claim 17, wherein regulating the intensity comprises:

regulating the intensity of light emitted from the plurality of light emitting diodes by cyclically switching, using the pulse-width modulator, the received power on and off according to a varying duty cycle, to compensate for at least one white light intensity-affecting factor.

21. The method for operating the replacement light tube of claim 17, wherein the power supply circuitry includes a pulse width modulator and a current limiter having an inductive element electrically coupled between the pulse width modulator and at least some of the plurality of light emitting diodes, the method further comprising:

limiting current to the plurality of light emitting diodes using the inductive element.

22. The method for operating the replacement light tube of claim 17, further comprising:

- switching power to the plurality of light emitting diodes on and off at a frequency; and
- causing the light emitted from the plurality of light emitting diodes to appear, when viewed by a human eye, to shine continuously.

23. A replacement light tube for replacing a fluorescent light tube, comprising:

- a housing having a first end and a second end;
- a first end cap and a second end cap disposed at the first end and the second end, respectively, each configured to fit with a socket for the fluorescent light tube;
- a plurality of light emitting diodes disposed inside and extending between the first and second ends of the housing, wherein the plurality of light emitting diodes is arranged to provide light through at least a portion of the housing; and
- a pulse width modulator configured to regulate the intensity of light emitted from the plurality of light emitting diodes by cyclically switching the received power on and off according to a varying duty cycle and configured to compensate for at least one white light intensity-effecting factor by using the cyclically-switched power.

24. The replacement light tube of claim 23, wherein the at least one light intensity-effecting factor is voltage fluctuations from the power source.

25. The replacement light tube of claim 23, wherein the at least one light intensity-effecting factor is ambient temperature changes.

26. The replacement light tube of claim 23, further comprising:

- a current limiter having an inductive element electrically coupled between the pulse width modulator and at least some of the plurality of light emitting diodes, the current limiter configured to receive power from the pulse width modulator and to transmit power to the at least some of the plurality of light emitting diodes.

27. The replacement light tube of claim 26, wherein the current limiter and the pulse width modulator are packaged outside of the housing.

28. The replacement light tube of claim 23, further comprising:

- a rigid support structure having a planar portion having a first surface extending within the housing between the first end and the second end and having spaced-apart sidewalls extending away from the first surface and extending within the housing between the first end and the second end, at least a portion of the sidewalls in contact with an interior surface of the housing.

29. The replacement light tube of claim 28, wherein the plurality of light emitting diodes are supported by a second surface of the planar portion opposite to the first surface and between the first end and the second end.

30. The replacement light tube of claim 28, wherein the planar portion is integral with the sidewalls.

* * * * *