

Strip LED Fixtures (1-lamp models)

- Universal voltage (120-277 VAC)
- 2, 3, and 4 foot models
- 1 and 2-lamp models
- No ballast, includes direct wire LED tubes
- 50,000 hour lifetime



FS410D0

Toggled fixtures are designed to be compatible with any toggled LED direct wire tube.

Outstanding Product Performance

- Provides up to 60% energy savings
- Eliminates ballasts and maintenance costs
- Designed for direct connection to building AC power, voltage 120-277 VAC
- Operating temperature -20 to 45° C

Superior Quality of Light

- Consistent color rendering, 80 CRI minimum
- UL listed

Commercial-grade

- Reliable start during cold temperatures
- All metal construction
- Durable white powder-coated finish

Ordering Information

Fixture	Type	Length	# Lamps	Style	Lens	Wire Termination	Tube Model #
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
F = Fixture	S = Strip/ Surface	2 = 2 feet 3 = 3 feet 4 = 4 feet	1 = 1 lamp 2 = 2 lamps	0 = Standard	D = None	0 = None	See next page




Strip LED Fixtures (1-lamp models)

Specifications

	Model No.	Length	Input Voltage	Total Power (Watts)	Total Lumens	Efficacy	CRI	CCT	PF
4 feet	FS410D0-E416-30310	4 feet	120-277 VAC	16	2,100	131	≥80	3000K	>0.9
	FS410D0-E416-40310	4 feet	120-277 VAC	16	2,100	131	≥80	4000K	>0.9
	FS410D0-E416-50310	4 feet	120-277 VAC	16	2,100	131	≥80	5000K	>0.9
	FS410D0-E416-65310	4 feet	120-277 VAC	16	2,100	131	≥80	6500K	>0.9
	FS410D0-A423-40230	4 feet	120-277 VAC	23	3,100	135	≥80	4000K	>0.9
	FS410D0-A423-50230	4 feet	120-277 VAC	23	3,100	135	≥80	5000K	>0.9
3 feet	FS310D0-E312-30310	3 feet	120-277 VAC	12	1,680	140	≥80	3000K	>0.9
	FS310D0-E312-40310	3 feet	120-277 VAC	12	1,680	140	≥80	4000K	>0.9
	FS310D0-E312-50310	3 feet	120-277 VAC	12	1,680	140	≥80	5000K	>0.9
	FS310D0-E312-65310	3 feet	120-277 VAC	12	1,680	140	≥80	6500K	>0.9
2 feet	FS210D0-E208-30310	2 feet	120-277 VAC	8	1,120	140	≥80	3000K	>0.9
	FS210D0-E208-40310	2 feet	120-277 VAC	8	1,120	140	≥80	4000K	>0.9
	FS210D0-E208-50310	2 feet	120-277 VAC	8	1,120	140	≥80	5000K	>0.9
	FS210D0-E208-65310	2 feet	120-277 VAC	8	1,120	140	≥80	6500K	>0.9

Dimensions



Fixture Model No.	Length	Width	Height
FS410D0	48.5in (1231mm)	1.7in (42mm)	2.9in (74mm)
FS310D0	36.5in (928mm)	1.7in (42mm)	2.9in (74mm)
FS210D0	24.4in (621mm)	1.7in (42mm)	2.9in (74mm)

Disclaimer: toggled reserves the right to make changes to specific items and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.